



"Results You Can Count On"

Power Line Communications Testing Solutions

**For Physical-Layer Testing of
G.hn Devices Over Power Lines**



Model GHN-SP-UPLC

The Model GHN-SP-UPLC Universal Powerline Communications Splitter device is used to provide a controlled AC port to the PLC modem, separate and isolate the high-frequency PLC signal from AC power, and make it accessible on three BNC ports labelled L1, L2 and L3 with a controlled impedance. Having the PLC signal on BNC ports allows using standard instruments and accessories to perform measurements and build controlled topologies. Capable of performing Dynamic PSD Test and Cognitive Frequency Exclusion test (Dynamic Notching) per EN 50561-1 using Model 501 and 501-Probe-Coax.

Main Features

- Similar to AMN / LISN specified in CISPR-16, extending the concept to all three lines
- Suitable for all types of broadband MIMO PLC (not valid for narrowband PLC < 2 MHz)
- Basic building block for TR-208 and EN-50561 tests
- High performance AC filter which provides high isolation with similar common-mode and differential-mode impedance on each line, L1, L2 and L3
- Provides galvanic isolation and common-mode filtering to prevent PLC leakage on data port
- BNC connectors for High Frequency signals on L1, L2, and L3
- Embedded Zero-Cross Detector for AC-synchronized measurements and tests
- Used with Telebyte Noise Generator for WT-208 testing
- Used with Telebyte Digital Analyzer for ITU-G.9964 PSD, CENELEC EN 50561-1, EN 50561-3 measurements



Adaptors available for multiple regions.



Model GHN-SP-SPLCOMB-UPLC-3

The Model GHN-SP-SPLCOMB-3 3-Channel Splitter/Combiner is a symmetrical power splitter and combiner where all the ports have 6 dB attenuation to each other.

This product provides one set of three BNC ports on one side and two sets on either side. The spacing between connectors is the same as in the GHN-SP-UPLC Universal Powerline Communications Splitter, allowing the device to be connected directly using male-male BNC barrels to reduce the number of cables. (Unused ports of the 3-Channel Power Splitter/Combiner must be terminated with 50Ω.)



Model GHN-AT-PROG-UPLC-3-Slope

The Model GHN-AT-PROG-UPLC-3 3-Channel Programmable Attenuator is used along with the GHN-SP-UPLC in the PSD Measurement test set up. Offers an attenuation range of 1 to 127 dB in 1-dB increments.



"Results You Can Count On"

Specifications

GHN-SP-UPLC	
Electrical Safety	Complies with EN 61010-1 : EN 60950-1
Insertion Loss (Single Line)	EUT to BNC OUT (L1-L3): 0.35dB@ 80 MHz, 0.45dB@ 100 MHz
Differential Line Impedance	100 ohm +/- 10% (1MHz to 100 MHz)
Continuous Operating Voltage	90 to 240VAC, 50 Hz/60 Hz
Outputs: L1, L2, L3	BNC-female Connector, 50 Ω Impedance, 1MHz to 100MHz

Specifications are subject to change without notice. Made in USA.

GHN-AT-PROG-UPLC-3-Slope	
Number of Channels	3
Attenuation Range	1 to 127 dB in 1-dB increments
Frequency Response Uniform	\pm 0.5 dB from 1 MHz to 127 MHz
Impedance	50 ohm
Connectors	SMA Connector Jack, Female Socket 50 Ohm
Interface	USB

Specifications are subject to change without notice. Made in USA.

Ordering Options

MODEL	DESCRIPTION
GHN-SP-UPLC	Universal PLC Splitter with Schuko socket
GHN-ADP-CH_BR	Approved Power Adaptor for GHN-SP-UPLC (Switzerland, Brazil)
GHN-ADP-UK	Approved Power Adaptor for GHN-SP-UPLC (United Kingdom)
GHN-ADP-IT_RCH	Approved Power Adaptor for GHN-SP-UPLC (Italy, Chile)
GHN-ADP-AU_RCN_AR	Approved Power Adaptor for GHN-SP-UPLC (Australia, China, Argentina)
GHN-ADP-NA	Approved Power Adaptor for GHN-SP-UPLC (North America)
GHN-SP-SPLCOMB-UPLC-3	3-Channel Splitter/Combiner
GHN-AT-PROG-UPLC-3-Slope	PLC 3-Channel Attenuator with Slope Filter
1XBNCM-1XSMAM-1F	BNC(male)-to-SMA(male) cable, length 1 foot
BNC-BNC-BARRELPLUG	BNC Plug-to-BNC Plug in-line barrel
BNC-TERM-50	50-ohm BNC Terminator
1XRJ45M-1XRJ45M-3F	Cat6 Shielded Patch Cable - SSTP Bare Copper, RJ-45 male connectors, length 3 feet